

Dépannage

```
ssh desktop@server18.ittraining.network / ZQeszFdYg21d
```

```
[root@centos7 bin]# lynx --dump -auth admin1:fenestros "http://www.i2tch.loc:8080/manager/text/serverinfo"
```

```
Looking up www.i2tch.loc:8080
Making HTTP connection to www.i2tch.loc:8080
Sending HTTP request.
HTTP request sent; waiting for response.
Alert!: Access without authorization denied -- retrying
Retrying with access authorization information.
Looking up www.i2tch.loc:8080
Making HTTP connection to www.i2tch.loc:8080
Sending HTTP request.
HTTP request sent; waiting for response.
Alert!: Can't retry with authorization! Contact the server's WebMaster.
Can't Access `http://www.i2tch.loc:8080/manager/text/serverinfo'
Alert!: Unable to access document.
```

```
lynx: Can't access startfile
```

```
[root@centos7 bin]# cat ../conf/server.xml
```

```
<?xml version='1.0' encoding='utf-8'?>
```

```
<!--
```

```
Licensed to the Apache Software Foundation (ASF) under one or more
contributor license agreements. See the NOTICE file distributed with
this work for additional information regarding copyright ownership.
The ASF licenses this file to You under the Apache License, Version 2.0
(the "License"); you may not use this file except in compliance with
the License. You may obtain a copy of the License at
```

<http://www.apache.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

```
-->
<!-- Note: A "Server" is not itself a "Container", so you may not
      define subcomponents such as "Valves" at this level.
      Documentation at /docs/config/server.html
-->
<Server port="8005" shutdown="SHUTDOWN">
  <Listener className="org.apache.catalina.startup.VersionLoggerListener" />
  <!-- Security listener. Documentation at /docs/config/listeners.html
  <Listener className="org.apache.catalina.security.SecurityListener" />
  -->
  <!--APR library loader. Documentation at /docs/apr.html -->
  <Listener className="org.apache.catalina.core.AprLifecycleListener" SSLEngine="on" />
  <!-- Prevent memory leaks due to use of particular java/javax APIs-->
  <Listener className="org.apache.catalina.core.JreMemoryLeakPreventionListener" />
  <Listener className="org.apache.catalina.mbeans.GlobalResourcesLifecycleListener" />
  <Listener className="org.apache.catalina.core.ThreadLocalLeakPreventionListener" />

  <!-- Global JNDI resources
      Documentation at /docs/jndi-resources-howto.html
  -->
  <GlobalNamingResources>
    <!-- Editable user database that can also be used by
          UserDatabaseRealm to authenticate users
    -->
    <Resource name="UserDatabase" auth="Container"
              type="org.apache.catalina.UserDatabase"
              description="User database that can be updated and saved"
```

```
        factory="org.apache.catalina.users.MemoryUserDatabaseFactory"
        pathname="conf/tomcat-users.xml" />
</GlobalNamingResources>

<!-- A "Service" is a collection of one or more "Connectors" that share
      a single "Container" Note: A "Service" is not itself a "Container",
      so you may not define subcomponents such as "Valves" at this level.
      Documentation at /docs/config/service.html
-->
<Service name="Catalina">

  <!--The connectors can use a shared executor, you can define one or more named thread pools-->
  <!--
  <Executor name="tomcatThreadPool" namePrefix="catalina-exec-"
    maxThreads="150" minSpareThreads="4"/>
  -->

  <!-- A "Connector" represents an endpoint by which requests are received
        and responses are returned. Documentation at :
        Java HTTP Connector: /docs/config/http.html (blocking & non-blocking)
        Java AJP Connector: /docs/config/ajp.html
        APR (HTTP/AJP) Connector: /docs/apr.html
        Define a non-SSL/TLS HTTP/1.1 Connector on port 8080
  -->
  <Connector port="8080" protocol="HTTP/1.1"
    connectionTimeout="20000"
    redirectPort="8443" />
  <!-- A "Connector" using the shared thread pool-->
  <!--
  <Connector executor="tomcatThreadPool"
    port="8080" protocol="HTTP/1.1"
    connectionTimeout="20000"
    redirectPort="8443" />
```

```
-->
<!-- Define a SSL/TLS HTTP/1.1 Connector on port 8443
This connector uses the NIO implementation that requires the JSSE
style configuration. When using the APR/native implementation, the
OpenSSL style configuration is required as described in the APR/native
documentation -->
<!--
<Connector port="8443" protocol="org.apache.coyote.http11.Http11NioProtocol"
maxThreads="150" SSLEnabled="true" scheme="https" secure="true"
clientAuth="false" sslProtocol="TLS" />
-->

<!-- Define an AJP 1.3 Connector on port 8009 -->
<Connector port="8009" protocol="AJP/1.3" redirectPort="8443" />

<!-- An Engine represents the entry point (within Catalina) that processes
every request. The Engine implementation for Tomcat stand alone
analyzes the HTTP headers included with the request, and passes them
on to the appropriate Host (virtual host).
Documentation at /docs/config/engine.html -->

<!-- You should set jvmRoute to support load-balancing via AJP ie :
<Engine name="Catalina" defaultHost="localhost" jvmRoute="jvm1">
-->
<Engine name="Catalina" defaultHost="localhost">

  <!--For clustering, please take a look at documentation at:
  /docs/cluster-howto.html (simple how to)
  /docs/config/cluster.html (reference documentation) -->
  <!--
  <Cluster className="org.apache.catalina.ha.tcp.SimpleTcpCluster"/>
  -->
```

```
<!-- Use the LockOutRealm to prevent attempts to guess user passwords
via a brute-force attack -->
<Realm className="org.apache.catalina.realm.LockOutRealm">
  <!-- This Realm uses the UserDatabase configured in the global JNDI
resources under the key "UserDatabase". Any edits
that are performed against this UserDatabase are immediately
available for use by the Realm. -->
  <!-- Realm className="org.apache.catalina.realm.UserDatabaseRealm"
resourceName="UserDatabase" digest="sha" /> -->

<Realm className="org.apache.catalina.realm.JDBCRealm"
  driverName="com.mysql.jdbc.Driver"
  connectionURL="jdbc:mysql://localhost:3306/auth_tomcat"
  connectionName="tomcat" connectionPassword="secret"
  userTable="users" userNameCol="nom_user" userCredCol="mdp_user"
  userRoleTable="roles" roleNameCol="nom_role" />

</Realm>

<Host name="localhost" appBase="webapps"
  unpackWARs="true" autoDeploy="true">

  <!-- SingleSignOn valve, share authentication between web applications
Documentation at: /docs/config/valve.html -->
  <!--
  <Valve className="org.apache.catalina.authenticator.SingleSignOn" />
  -->

  <!-- Access log processes all example.
Documentation at: /docs/config/valve.html
Note: The pattern used is equivalent to using pattern="common" -->
  <!-- <Valve className="org.apache.catalina.valves.AccessLogValve" directory="logs"
prefix="localhost_access_log" suffix=".txt"
pattern="%h %l %u %t &quot;%r&quot; %s %b" /> -->
```

```
<Valve className="org.apache.catalina.valves.AccessLogValve"  
  directory="logs" prefix="tomcat_access." suffix=".txt"  
  resolveHosts="false" fileDateFormat="yyyy_MM_dd"  
  pattern="%t - %a %H %s - %r"/>  
  
  </Host>  
</Engine>  
</Service>  
</Server>
```